



LS-10 Specifications

Recording Format	Linear PCM (Pulsed Code Modulation) WAVE
	MP3 (MPEG-1/MPEG-2 Audio Layer 3)
	WMA (Windows Media Audio)
Recording Media	Built-in 2 GB NAND Flash memory
	SD Card (512 MB to 8 GB)
Recording Time	Built-in 2 GB memory
	Linear PCM: Up to 3 hours 10 minutes
	MP3: Up to 35 hours 35 minutes
	WMA: Up to 69 hours 35 minutes
Card Format	SD, SDHC
Input Level	MIC SENSE HIGH -59 dBv
	MIC SENSE LOW -39 dBv
	LINE IN jack input -6 dBv

PC Interface	USB
LCD	35 x 29 mm
LED	1 color (red)
Folder Messages	5 folders, 200 messages per folder, plus MUSIC folder
Speaker	2 16mm round dynamic speakers, 8 ohms, 200 mW output
MIC Jack	3.5mm stereo mini-jack, impedance 2 kohms
LINE IN Jack	3.5mm stereo mini-jack, impedance 2 kohms
EAR Jack	3.5mm stereo mini-jack, impedance 8 ohms
Maximum Headphone Output	3 mW per channel at a load of 16 ohms
Batteries	2 AA Alkaline, Lithium, or NiMH batteries
External Power Supply	Olympus D-7AC AC Adapter
Size	131.5 mm x 48 mm x 22.4 mm (without protrusions)
Weight	165 grams (including alkaline batteries)
OS Supported	Windows: 2000/XP/VISTA Macintosh: Mac OS 10.2 or later
CPU and RAM	Windows: Intel Pentium or AMD Athlon 1.4 GHz processor, 512 MB RAM Macintosh: Power Mac G4 1 GHz or Core Solo 1.5 GHz, 512 MB RAM

Sound Board

Windows: Windows DirectX compatible, ASIO compatible sound card recommended for low latency performance

Macintosh: Core Audio compatible audio hardware